



## Reducción excéntrica soldable L32

|                   |                |
|-------------------|----------------|
| TIPO DE ACERO:    | T-304 / T-316L |
| TIPO DE CONEXIÓN: | Soldable       |
| ACABADO:          | 180 – 420 Grit |

### DIMENSIONES (mm)

| SIZE        | A     | D     | D2    |
|-------------|-------|-------|-------|
| 1" x ½"     | 50.8  | 25.4  | 12.7  |
| 1" x ¾"     | 25.5  | 25.4  | 19    |
| 1 ½" x ¾"   | 76.2  | 38.1  | 19    |
| 1 ½" x ½"   | 101.6 | 38.1  | 12.7  |
| 1 ½" x 1"   | 50.8  | 38.1  | 25.4  |
| 2" x ½"     | 50.8  | 50.8  | 12.7  |
| 2" x 1"     | 101.6 | 50.8  | 25.4  |
| 2" x 1 ½"   | 50.8  | 50.8  | 38.1  |
| 2 ½" x ½"   | 179   | 63.5  | 12.7  |
| 2 ½" x 1"   | 152.4 | 63.5  | 25.4  |
| 2 ½" x 1 ½" | 101.6 | 63.5  | 38.1  |
| 2 ½" x 2"   | 50.8  | 63.5  | 50.8  |
| 3" x 1"     | 203.2 | 76.2  | 25.4  |
| 3 x 1 ½"    | 152.4 | 76.2  | 25.4  |
| 3" x 2"     | 101.6 | 76.2  | 25.4  |
| 3" x 2 ½"   | 50.8  | 76.2  | 63.5  |
| 4" x 1"     | 304.8 | 101.6 | 25.4  |
| 4" x 1 ½"   | 254   | 101.6 | 38.1  |
| 4" x 2"     | 203.2 | 101.6 | 50.8  |
| 4" x 2 ½"   | 152.4 | 101.6 | 63.5  |
| 4" x 3"     | 101.6 | 101.6 | 76.2  |
| 6 x 1"      | 140   | 152.4 | 25.4  |
| 6 x 2"      | 140   | 152.4 | 50.8  |
| 6 x 3"      | 140   | 152.4 | 76.2  |
| 6" x 4"     | 140   | 152.4 | 101.6 |
| 8" x 6"     | 152.4 | 203.2 | 152.4 |

